

# BEVMAX

35 SELECT • MODEL 3800-4

# 4

## BEVMAX VALUE IN A SMALLER FOOTPRINT

PRODUCT DISPLAY • CONSUMER CONVENIENCE • RELIABILITY



SAME FOOTPRINT  
AS A STANDARD  
STACK MACHINE



MEETS ANSI  
AND NEW ADA  
REQUIREMENTS



EXCEEDS  
ENERGY STAR  
TIER 3 AND  
2013 D.O.E.

CRANE MERCHANDISING SYSTEMS

# BEVMAX

35 SELECT • MODEL 3800-4

# 4



...two times more energy efficient than machines made five years ago -

	kWh per year	Increased Operating Costs per Year	
BevMax4 - Narrow	1376		
Competitor A	2042	\$73.46	+48%
Competitor B	2100	\$79.86	+53%
5-Year Old Machine	2871	\$164.90	+109%

Based on the national average cost per kWh in January 2009 of \$0.1103/kWh. Actual energy usage may vary based on environmental conditions.

ENERGY EFFICIENT REFRIGERATION PLATFORM

## Tier 3



BevMax4 exceeds ENERGY STAR Tier 3 Standards. The only Glass Front to exceed the Department of Energy 2013 Conservation Standards.

Only BevMax4 has been designed to enhance the consumer experience and meet the operational needs of bottlers and vending operators.



**35** Selections  
+ **280** Capacity

in a 39" standard stack footprint



### RELIABILITY.

The most reliable, dependable vending solution proven by independent lab tests of 20,000 operating vends; 80,000 vend life-cycles and comprehensive field testing exceeding 238,000 vends.

### VERSATILITY.

Increase sales and profitability by replacing an aging 10-12 select stack vender. With a similar footprint to most stack machines, the BevMax4 Narrow offers an alternative size for locations where space is a premium.

### EFFICIENCY.

A "shimless" vend mechanism addresses costly labor and service concerns. Load any package in any position. Eliminate loading errors. Load fast with both hands. Bottles remain firmly in place (even if the machine is rocked).

### SPEED.

Who likes to wait in line? BevMax4 delivers product in only 8-seconds. Faster delivery time increases sales; speed of service and customer satisfaction.

### SIMPLIFIED MAINTENANCE

Low profile modular refrigeration platform removes from the front or the back of the machine.



### SPECIFICATIONS

- DIMENSIONS**  
72" H x 39" W x 32" D  
(183cm H x 120cm W x 82cm D)
- WEIGHT**  
545 lbs. empty (247 kg)
- ELECTRICAL**  
115 VAC, 60Hz, 10.2 amps  
MDB Level 3 Controller
- REFRIGERATION**  
134A CFC-Free Refrigerant Gas  
1/3 HP Compressor
- CERTIFICATIONS**  
UL, CUL, CE, FCC, NOM, CTICK



3330 DIXIE-NARCO BOULEVARD ■ WILLISTON, SC 29853  
TEL 800-688-9090 ■ FAX 803-266-5150 ■ WWW.DIXIENARCO.COM