



NEW TACTILE KEYPAD

INCREASED VERTICAL SHELF HEIGHT

HIGH PERFORMANCE REFRIGERATION SYSTEM



EXCEEDS ENERGY STAR TIER 2 STANDARDS

CRANE

Dixie Narco
Vending Systems

3330 CRANE WAY • WILLISTON, SC 29853 USA • TEL +1 803-266-5000 • WWW.CRANEMS.COM



...is two times more energy efficient than machines made five years ago -

40% more energy efficient than competitors.

	kWh per year	Increased Operating Costs per Year	
BevMax4	1443		
Competitor A	2042	\$66.06 +41%	
Competitor B	2100	\$72.47 +45%	
5-Year Old Machine	2885	\$158.96 +100	%



BevMax4 exceeds **ENERGY STAR** Tier 2 Standards and operates at twice the efficiency of 5-year old machines...that's COOL!

ENERGY EFFICIENT REFRIGERATION PLATFORM

Based on the national average cost per kWh in January 2009 of \$0.1103/kWh. Energy usage measured using EPA Energy Star test methods for refrigerated vending machines.

Only BevMax4 has been designed to enhance the consumer experience and meet the operational needs of bottlers and vending operators.



RELIABILITY.

The most reliable, dependable vending solution proven by independent 20,000 vend operating tests; 80,000 vend life-cycle tests and comprehensive field testing exceeding 238,000 vends.



VARIETY.

Reduce sold-out column potential. Add more facings of high turnover products. Create more variety to appeal to broad consumer segments and daypart consumption. Make more efficient, bigger case drops.



EFFICIENCY.

A "shimless" vend mechanism addresses costly labor and service concerns. Load any package in any position. Eliminate loading errors. Load fast with both hands. Bottles remain firmly in place (even if the machine is rocked).



SPEED.

Who likes to wait in line? BevMax4 delivers product in only 8-seconds. Faster delivery time increases sales; speed of service and customer satisfaction.

SIMPLIFIED MAINTENANCE

Low profile modular refrigeration platform removes from the front or the back of the machine.





SPECIFICATIONS

DIMENSIONS

72" H x 47" W x 32" D (183cm H x 120cm W x 82cm D)

764 lbs. empty (347 kg)

ELECTRICAL 110VAC, 60Hz, 10.2 amps

REFRIGERATION

134A CFC-Free Refrigerant Gas 1/3 HP Compressor

CERTIFICATIONS

UL, CUL, CE, FCC, NOM, CTICK



